

























Efficient production solutions for diverse industries. Customer examples.

	piece	machine	s/pc	starting from
Automotive	 length 70 mm	Multifactor	7.5	Al-alloy casted part
	 length 80 mm	Multifactor	8.5	Al-alloy blank
	 length 70 mm	Multistep XT-200	31	Al-alloy casted part. Multiple clamping
	 length 200 mm	Multistep XT-200	55	Al-alloy casted part. 2 machining phases complete unattended
	 length 180 mm	Multistep XT-200	420	Stainless steel casted part
	 Ø 32 mm	Mikron NRG-50	15	Chrome-Steel-alloy pretuned blank
	 Ø 18 mm	Multistar CX-24	8	Chrome-Steel-alloy pretuned blank
	 length 50 mm	Multistar NX-24	7	Chrome-Steel-alloy pretuned blank
Pneumatic & Hydraulic	 length 50 mm	Mikon NRG-50	13-30	Different shape of Al-SiMg Alloy bar, 30' to 90' changeover time
	 length 80 mm	Multistep XT-200	280	Starting from steel blank. High accuracy grooving and deep hole drilling
Gas	 length 50 mm	Multifactor	5	Profiled Al Alloy bar
	 length 15 mm	Multistar CX-24	1.2	Brass wire coil, including insertion of Nylon piece

	piece	machine	s/pc	starting from
Watches	 Ø 20-34 mm	Mikron NRG-50	40-60	Brass plate blank. ±3µm accuracy
	 length 30 mm	Mikron NSM-10	8	Stainless steel wire
Medical	 Ø 65 mm	Multifactor	13-37	Pretuned stainless steel blank
	 length 18 mm	Multistar NX-24	7	Titan wire coil
Spectacles	 length 18 mm	Mikron NAM-10	2.7	Double Titan wire coil
	 large 3 mm	Mikron NAM-8	2.4	Double quick-silver wire coil; left & right component simultaneously
Electro	 length 12 mm	Multistar LX-24	0.11	Brass cold pressed blank; dry machining
	 length 40 mm	Multistar CX-24	1.7	Brass wire, high tech connector
	 length 22 mm	Multistar CX-24	0.5	Profiled brass wire; male & female component simultaneously
Lock	 length 35 mm	Mikron NAM-8	3	Starting from bar or wire-coil
White	 Ø 16-35 mm	Multifactor	5	MIM Steel blank
Bicycle	 length 12-22 mm	Multistar LX-24	0.18	Cold pressed blank. 4 cycles machining